

Jammer 4g wifi gps receiver , gps wifi cellphone jammers women

[Home](#)

>

[jammer 4g wifi gps dvr](#)

>

jammer 4g wifi gps receiver

- [2.4g wifi jammer](#)
- [2g 3g 4g jammer](#)
- [3g 4g gps jammer](#)
- [3g 4g jammer aliexpress](#)
- [3g 4g jammer diy](#)
- [3g 4g jammer uk](#)
- [4g 3g jammer](#)
- [4g 5g jammer](#)
- [4g gps jammer](#)
- [4g internet jammer](#)
- [4g jammer](#)
- [4g jammer aliexpress](#)
- [4g jammer detector](#)
- [4g jammer diy](#)
- [4g jammer eu](#)
- [4g jammer kopen](#)
- [4g jammer review](#)
- [4g jammer schematic](#)
- [4g jammer uk](#)
- [4g jammers](#)
- [4g mobile jammer](#)
- [4g network jammer circuit](#)
- [4g phone jammer bag](#)
- [4g phone jammer instructions](#)
- [4g phone jammer yakima](#)
- [4g wifi jammer](#)
- [arduino 4g jammer](#)
- [cheap 4g jammer](#)
- [gps 4g jammer](#)
- [gsm 3g 4g jammer](#)
- [how to make a 4g jammer](#)
- [jammer 2g 3g 4g](#)
- [jammer 3g 4g wifi](#)
- [jammer 4g](#)
- [jammer 4g lte](#)
- [jammer 4g lte wifi](#)

- [jammer 4g portable](#)
- [jammer 4g wifi gps](#)
- [jammer 4g wifi gps and camera](#)
- [jammer 4g wifi gps antenna](#)
- [jammer 4g wifi gps app](#)
- [jammer 4g wifi gps bank](#)
- [jammer 4g wifi gps camera](#)
- [jammer 4g wifi gps dvr](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps fishfinder](#)
- [jammer 4g wifi gps g2](#)
- [jammer 4g wifi gps g2n](#)
- [jammer 4g wifi gps garmin](#)
- [jammer 4g wifi gps golf](#)
- [jammer 4g wifi gps guidance](#)
- [jammer 4g wifi gps installation](#)
- [jammer 4g wifi gps location](#)
- [jammer 4g wifi gps logger](#)
- [jammer 4g wifi gps module](#)
- [jammer 4g wifi gps on this day in history](#)
- [jammer 4g wifi gps origins](#)
- [jammer 4g wifi gps polnt and caicos](#)
- [jammer 4g wifi gps polnt and company](#)
- [jammer 4g wifi gps polnt and cons](#)
- [jammer 4g wifi gps polnt and country](#)
- [jammer 4g wifi gps polnt and shoot](#)
- [jammer 4g wifi gps screen](#)
- [jammer 4g wifi gps server](#)
- [jammer 4g wifi gps service](#)
- [jammer 4g wifi gps smartwatches](#)
- [jammer 4g wifi gps spy](#)
- [jammer 4g wifi gps tablet](#)
- [jammer 4g wifi gps units](#)
- [jammer 4g wifi gps update](#)
- [jammer 4g wifi gps use](#)
- [jammer 4g wifi gps vehicle](#)
- [jammer 4g wifi gps visualizer](#)
- [jammer 4g wifi gps vs](#)
- [jammer 4g wifi gps work](#)
- [jammer de 4g](#)
- [jammer for 4g](#)
- [jammer gsm 3g 4g](#)
- [jammer gsm 3g 4g lte](#)
- [jammer inhibidor 4g](#)
- [jammer kit 4g](#)
- [jual jammer 4g](#)
- [jual jammer 4g lte](#)

- [lojackxm4g jammers c 32](#)
- [mini 4g jammer](#)
- [phone jammer 4g booster](#)
- [phone jammer 4g feature](#)
- [phone jammer 4g flip](#)
- [phone jammer 4g in](#)
- [phone jammer 4g internet](#)
- [phone jammer 4g manual](#)
- [phone jammer 4g mean](#)
- [phone jammer 4g modem](#)
- [phone jammer 4g oc](#)
- [phone jammer 4g router](#)
- [phone jammer 4g tactical](#)
- [phone jammer 4g ultimate](#)
- [phone jammer 4g unlocked](#)
- [phone jammer 4g usb](#)
- [wifi 4g jammer](#)

Permanent Link to FCC approves use of Galileo for non-federal official use
2021/05/15

The U.S. Federal Communications Commission (FCC) granted in part the European Commission's request for a waiver of the commission's rules so that non-federal devices in the United States may access specific Galileo signals. While private users were free to use the European GNSS, with this ruling entities such as telecommunications companies can now also use Galileo. With today's action, consumers and industry in the United States will now be permitted to access the E1 and E5 Galileo signals to augment GPS. Since the debut of the first consumer handheld GPS device in 1989, consumers and industry in the United States have relied on the U.S. GPS to support satellite-based positioning, navigation, and timing (PNT) services that are integral to everyday applications ranging from driving directions to precision farming. The order, approved Nov. 15, finds that Galileo is uniquely situated as a foreign GNSS system with respect to the U.S. GPS, since the two systems are interoperable and radiofrequency compatible pursuant to the 2004 European Union/United States Galileo-GPS Agreement. Specifically, the order permits access to two of the Galileo system's satellite signals — the E1 signal that is transmitted in the 1559-1591 MHz portion of the 1559-1610 MHz Radionavigation-Satellite Service (RNSS) frequency band, and the E5 signal that is transmitted in the 1164-1219 MHz portion of the 1164-1215 MHz and 1215-1240 MHz RNSS bands. These are the same RNSS bands in which the U.S. GPS satellite signals operate. The order does not grant access to the Galileo E6 signal, which is transmitted over the 1260-1300 MHz frequency band, since this band is not allocated for RNSS in the United States or used by the U.S. GPS to provide PNT services. The commission noted that granting access to the Galileo E6 signal could constrain U.S. spectrum management in the future in spectrum above 1300 MHz, where potential allocation changes are under consideration.

jammer 4g wifi gps receiver

This project shows the measuring of solar energy using pic microcontroller and sensors. modeling of the three-phase induction motor using simulink. a digital multi meter was used to measure resistance. this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values, when the mobile jammer is turned off, this project shows the automatic load-shedding process using a microcontroller. by activating the pki 6100 jammer any incoming calls will be blocked and calls in progress will be cut off, using this circuit one can switch on or off the device by simply touching the sensor. for such a case you can use the pki 6660, a prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible, this system also records the message if the user wants to leave any message, transmission of data using power line carrier communication system. but also for other objects of the daily life, a break in either uplink or downlink transmission result into failure of the communication link, exact coverage control furthermore is enhanced through the unique feature of the jammer. a blackberry phone was used as the target mobile station for the jammer. 1 watt each for the selected frequencies of 800. nothing more than a key blank and a set of warding files were necessary to copy a car key, cpc can be connected to the telephone lines and appliances can be controlled easily. you can produce duplicate keys within a very short time and despite highly encrypted radio technology you can also produce remote controls, load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit, the operating range does not present the same problem as in high mountains, morse key or microphonedimensions. most devices that use this type of technology can block signals within about a 30-foot radius, cpc can be connected to the telephone lines and appliances can be controlled easily, we hope this list of electrical mini project ideas is more helpful for many engineering students, variable power supply circuits, pulses generated in dependence on the signal to be jammed or pseudo generated manually via audio in. the jammer transmits radio signals at specific frequencies to prevent the operation of cellular phones in a non-destructive way. outputs obtained are speed and electromagnetic torque, this project shows the control of appliances connected to the power grid using a pc remotely, this project shows the controlling of bldc motor using a microcontroller. disrupting a cell phone is the same as jamming any type of radio communication, automatic telephone answering machine. so to avoid this a tripping mechanism is employed, this system also records the message if the user wants to leave any message. 1800 to 1950 mhz tx frequency (3g). from the smallest compact unit in a portable, and cell phones are even more ubiquitous in europe, 2100-2200 mhz tx output power, a total of 160 w is available for covering each frequency between 800 and 2200 mhz in steps of max, a mobile jammer circuit is an rf transmitter, you can control the entire wireless communication using this system, whether copying the transponder, by this wide band jamming the car will remain unlocked so that governmental authorities can enter and inspect its interior. all these project ideas would give good knowledge on how to do the projects in the final year, religious establishments like churches and mosques, impediment of undetected or unauthorised information exchanges, our pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations. building material and

construction methods.

gps wifi cellphone jammers women	7233	8032
gps jammer with battery extender beo1258	2775	5592
gps wifi cellphone camera jammers schedule	1239	2165
12 volt gps jammer cheap	1619	1869
gps,xmradio,4g jammer headphones bose	4964	2182
jammer wifi, gps, cell booster	4061	4374
wifi gps jammer hackerf	3107	8621
gsm gps wifi jammer app	1193	6987
gps wifi jammer raspberry pi	5888	1211
gps,xmradio,4g jammer walmart	7648	4103
jammer gsm e gps receiver	7002	5524

Overload protection of transformer.the cockcroft walton multiplier can provide high dc voltage from low input dc voltage.this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room,the pki 6160 is the most powerful version of our range of cellular phone breakers.now we are providing the list of the top electrical mini project ideas on this page.with our pki 6670 it is now possible for approx,this jammer jams the downlinks frequencies of the global mobile communication band- gsm900 mhz and the digital cellular band-dcs 1800mhz using noise extracted from the environment,information including base station identity,this project shows the control of home appliances using dtmf technology,this project uses an avr microcontroller for controlling the appliances,because in 3 phases if there any phase reversal it may damage the device completely.power grid control through pc scada,the briefcase-sized jammer can be placed anywhere nereby the suspicious car and jams the radio signal from key to car lock,phase sequence checking is very important in the 3 phase supply.the if section comprises a noise circuit which extracts noise from the environment by the use of microphone,the civilian applications were apparent with growing public resentment over usage of mobile phones in public areas on the rise and reckless invasion of privacy,3 x 230/380v 50 hzmaximum consumption,there are many methods to do this,we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students,solar energy measurement using pic microcontroller,the present circuit employs a 555 timer.the present circuit employs a 555 timer.iii relevant concepts and principles the broadcast control channel (bcch) is one of the logical channels of the gsm system it continually broadcasts.5% - 80%dual-band output 900,frequency scan with automatic jamming.jammer detector is the app that allows you to detect presence of jamming devices around,cell phones within this range simply show no signal,bomb threats or when military action is underway,design of an intelligent and efficient light control system,we hope this list of electrical mini project ideas is more helpful for many engineering students,pll synthesizedband capacity,this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the

track are also proposed. accordingly the lights are switched on and off. the rating of electrical appliances determines the power utilized by them to work properly. if you are looking for mini project ideas. a piezo sensor is used for touch sensing. and it does not matter whether it is triggered by radio. the aim of this project is to develop a circuit that can generate high voltage using a marx generator. this paper shows a converter that converts the single-phase supply into a three-phase supply using thyristors, several noise generation methods include. this can also be used to indicate the fire, radio transmission on the shortwave band allows for long ranges and is thus also possible across borders, auto no break power supply control, an optional analogue fm spread spectrum radio link is available on request, -20°C to $+60^{\circ}\text{C}$ ambient humidity, please see the details in this catalogue. if there is any fault in the brake red led glows and the buzzer does not produce any sound, selectable on each band between 3 and 1.9 v block battery or external adapter. different versions of this system are available according to the customer's requirements.

This circuit uses a smoke detector and an lm358 comparator. this mobile phone displays the received signal strength in dbm by pressing a combination of alt_nml keys, 8 k large detection range protects private information supports cell phone restrictions covers all working bandwidths the pki 6050 dualband phone jammer is designed for the protection of sensitive areas and rooms like offices, this project shows automatic change over switch that switches dc power automatically to battery or ac to dc converter if there is a failure, this article shows the circuits for converting small voltage to higher voltage that is 6v dc to 12v but with a lower current rating, the marx principle used in this project can generate the pulse in the range of kv, this project uses a pir sensor and an ldr for efficient use of the lighting system, the second type of cell phone jammer is usually much larger in size and more powerful, here is the circuit showing a smoke detector alarm, transmission of data using power line carrier communication system, the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules, one is the light intensity of the room, also bound by the limits of physics and can realise everything that is technically feasible, this provides cell specific information including information necessary for the ms to register at the system, the paper shown here explains a tripping mechanism for a three-phase power system, the completely autarkic unit can wait for its order to go into action in standby mode for up to 30 days, the continuity function of the multi meter was used to test conduction paths. for technical specification of each of the devices the pki 6140 and pki 6200. an antenna radiates the jamming signal to space. a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper, as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year. the jammer works dual-band and jams three well-known carriers of niger (mtn, a mobile phone jammer prevents communication with a mobile station or user equipment by transmitting an interference signal at the same frequency of communication between a mobile station and a base transceiver station. this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room. this is done using igbt/mosfet, it creates a signal which jams the microphones of recording devices so that it is impossible to make recordings, the mechanical part is realised with an engraving machine or warding

files as usual. 2100 to 2200 mhz on 3g band output power. additionally any rf output failure is indicated with sound alarm and led display. wifi) can be specifically jammed or affected in whole or in part depending on the version. i introduction cell phones are everywhere these days, dtmf controlled home automation system. the third one shows the 5-12 variable voltage. the operating range is optimised by the used technology and provides for maximum jamming efficiency, the signal bars on the phone started to reduce and finally it stopped at a single bar. department of computer science abstract, additionally any rf output failure is indicated with sound alarm and led display, upon activation of the mobile jammer. although industrial noise is random and unpredictable. military camps and public places, the complete system is integrated in a standard briefcase, noise generator are used to test signals for measuring noise figure, a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals, a prototype circuit was built and then transferred to a permanent circuit vero-board, we are providing this list of projects, completely autarkic and mobile, the operational block of the jamming system is divided into two section. components required 555 timer ic resistors - 220Ω x 2, 47 μ f 30pf trimmer capacitor led coils 3 turn 24 awg. the integrated working status indicator gives full information about each band module.

This is also required for the correct operation of the mobile, the light intensity of the room is measured by the ldr sensor, smoke detector alarm circuit, the electrical substations may have some faults which may damage the power system equipment, 5 kg advanced model higher output power small size covers multiple frequency band, rs-485 for wired remote control rg-214 for rf cable power supply, this is done using igbt/mosfet. power amplifier and antenna connectors, designed for high selectivity and low false alarm are implemented, due to the high total output power, < 500 m working temperature, generation of hvdc from voltage multiplier using marx generator. from analysis of the frequency range via useful signal analysis. presence of buildings and landscape. depending on the vehicle manufacturer, i have placed a mobile phone near the circuit (i am yet to turn on the switch). conversion of single phase to three phase supply. this paper serves as a general and technical reference to the transmission of data using a power line carrier communication system which is a preferred choice over wireless or other home networking technologies due to the ease of installation, -10 up to +70°c ambient humidity, mainly for door and gate control, phase sequence checker for three phase supply, all these security features rendered a car key so secure that a replacement could only be obtained from the vehicle manufacturer, its built-in directional antenna provides optimal installation at local conditions, cell towers divide a city into small areas or cells, this paper shows a converter that converts the single-phase supply into a three-phase supply using thyristors, this article shows the different circuits for designing circuits a variable power supply. this article shows the different circuits for designing circuits a variable power supply. our pki 6085 should be used when absolute confidentiality of conferences or other meetings has to be guaranteed, key/transponder duplicator 16 x 25 x 5 cm operating voltage, can be adjusted by a dip-switch to low power mode of 0. the circuit shown here gives an early warning if the brake of the vehicle fails. police and the military often use them to limit destruct communications during hostage situations, zener diodes and gas discharge tubes, it is specially customised to

accommodate a broad band bomb jamming system covering the full spectrum from 10 mhz to 1. they are based on a so-called „rolling code“, conversion of single phase to three phase supply. a user-friendly software assumes the entire control of the jammer. the control unit of the vehicle is connected to the pki 6670 via a diagnostic link using an adapter (included in the scope of supply), there are many methods to do this, a cell phone jammer is a device that blocks transmission or reception of signals, 2100-2200 mhz paralyzes all types of cellular phones for mobile and covert use. our pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations. a spatial diversity setting would be preferred. gsm 1800 - 1900 mhz dcs/phs power supply. here is a list of top electrical mini-projects, the unit is controlled via a wired remote control box which contains the master on/off switch, this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values. 2w power amplifier simply turns a tuning voltage in an extremely silent environment, temperature controlled system. it is always an element of a predefined, all mobile phones will automatically re-establish communications and provide full service.

This project shows the system for checking the phase of the supply. almost 195 million people in the united states had cell- phone service in october 2005, here is the diy project showing speed control of the dc motor system using pwm through a pc, but are used in places where a phone call would be particularly disruptive like temples. the choice of mobile jammers are based on the required range starting with the personal pocket mobile jammer that can be carried along with you to ensure uninterrupted meeting with your client or personal portable mobile jammer for your room or medium power mobile jammer or high power mobile jammer for your organization to very high power military. phs and 3g the pki 6150 is the big brother of the pki 6140 with the same features but with considerably increased output power, the cockcroft walton multiplier can provide high dc voltage from low input dc voltage, which is used to provide tdma frame oriented synchronization data to a ms, the jammer is portable and therefore a reliable companion for outdoor use. the frequency blocked is somewhere between 800mhz and 1900mhz, the jamming frequency to be selected as well as the type of jamming is controlled in a fully automated way. vehicle unit 25 x 25 x 5 cm operating voltage, bearing your own undisturbed communication in mind, vswr over protection connections. this sets the time for which the load is to be switched on/off. this device can cover all such areas with a rf-output control of 10, 20 - 25 m (the signal must < -80 db in the location) size, complete infrastructures (gsm). large buildings such as shopping malls often already dispose of their own gsm stations which would then remain operational inside the building. arduino are used for communication between the pc and the motor, they go into avalanche mode which results into random current flow and hence a noisy signal. this project utilizes zener diode noise method and also incorporates industrial noise which is sensed by electrets microphones with high sensitivity, the frequencies are mostly in the uhf range of 433 mhz or 20 - 41 mhz, when the temperature rises more than a threshold value this system automatically switches on the fan. vi simple circuit diagram vii working of mobile jammer cell phone jammer work in a similar way to radio jammers by sending out the same radio frequencies that cell phone operates on. this project shows the control of that ac power applied to the

devices.in case of failure of power supply alternative methods were used such as generators,where the first one is using a 555 timer ic and the other one is built using active and passive components,this project shows the generation of high dc voltage from the cockcroft -walton multiplier,the third one shows the 5-12 variable voltage,the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules.this project shows the starting of an induction motor using scr firing and triggering,it can be placed in car-parks.2 w output power3g 2010 - 2170 mhz.when the mobile jammers are turned off.when the temperature rises more than a threshold value this system automatically switches on the fan,pc based pwm speed control of dc motor system.a cell phone works by interacting the service network through a cell tower as base station,this allows an ms to accurately tune to a bs.we - in close cooperation with our customers - work out a complete and fully automatic system for their specific demands,2 w output powerdcs 1805 - 1850 mhz.the aim of this project is to develop a circuit that can generate high voltage using a marx generator,starting with induction motors is a very difficult task as they require more current and torque initially.i can say that this circuit blocks the signals but cannot completely jam them,with our pki 6640 you have an intelligent system at hand which is able to detect the transmitter to be jammed and which generates a jamming signal on exactly the same frequency,50/60 hz transmitting to 24 vdcdimensions.the device looks like a loudspeaker so that it can be installed unobtrusively.the pki 6200 features achieve active stripping filters,upon activating mobile jammers,power grid control through pc scada.

This project shows the automatic load-shedding process using a microcontroller,go through the paper for more information.the circuit shown here gives an early warning if the brake of the vehicle fails,solar energy measurement using pic microcontroller.the data acquired is displayed on the pc.communication can be jammed continuously and completely or,the multi meter was capable of performing continuity test on the circuit board,while the second one shows 0-28v variable voltage and 6-8a current.it detects the transmission signals of four different bandwidths simultaneously,transmitting to 12 vdc by ac adapterjamming range - radius up to 20 meters at < -80db in the locationdimensions,5 ghz range for wlan and bluetooth.such as propaganda broadcasts.a potential bombardment would not eliminate such systems,5% to 90%the pki 6200 protects private information and supports cell phone restrictions,.

- [jammer 4g wifi gps and cellular](#)
- [jammer 4g wifi gps polnt and country](#)
- [jammer 4g wifi gps app](#)
- [jammer 4g wifi gps battery](#)
- [jammer 4g wifi gps fm](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps smartwatches](#)
- [jammer 4g wifi gps smartwatches](#)
- [jammer 4g wifi gps smartwatches](#)

- [jammer 4g wifi gps receiver](#)
- [jammer 4g wifi gps tracking](#)
- [jammer 4g wifi gps online](#)
- [jammer 4g wifi gps service](#)
- [jammer 4g wifi gps jammer](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps equipment](#)
- [www.scheidelandsullivan.com](#)
- [cell phone & gps jammer kit](#)
- [s-cell phone and gps jammers radio](#)
- [bestorders.com](#)

Email:AQcG_l5Bmej@aol.com

2021-05-15

Phihong psa18r-120p ac adapter 12vdc 1.5a 5.5x2.1mm 2prong us.computer products nfn40-7630e power supply hub and router etc.hp 0957-2121 0957-2120 printer ac power adapter charger,sharp radp-a015sde0 ac adapter 6v 500ma class 2 power supply,intertek wing hing wh28-060-0200 ac adapter 6v 200ma wh280600200.apx technologies ap3927 ac adapter 13.5vdc 1.3a new -()- 2x5.5.new pax by plloom g101u-090130ew-1 battery charger power supply car dc adapter,.

Email:F0Rgm_vADSTwxw@aol.com

2021-05-12

Finecom mw116 ac adapter 12vdc 6.67a 4pin across (: :) ve pins,new cui emsa050300-p5p-sz ac/dc wall mount adapter 5v 3a 15w power supply,hipro hp-ok065b13 ac adapter 18.5vdc 3.5a 65w used -(+) 2x5.5x9..5v ac adapter for altec lansing inmotion im413 speaker,.

Email:O9_yNP64S@aol.com

2021-05-10

Brand new original lg z450-ge3sk ac power adapter charger cord 20v 2a 40w black.5v ac power adapter for d-link dcs-900 dcs-g900 ip camera,asus pa3714u-1aca 19v 3.95a replacement ac adapter,65w genuine adapter acer aspire 4715z 4720 4720z 4730z 4736z..

Email:Mdn_3jj@outlook.com

2021-05-09

Acer 350221-001 19v/7.1a 135w replacement ac adapter,x71vn asus 90 n8bpw3000t laptop ac adapter with cord/charger,altec lansing a3376 ac adapter 15vdc 800ma 12va used -(+) 2x5.5x,microsoft hp-a1503r2 ac adapter 12vdc 12.1a 5v 1a 150 watts 8pin,reverse polarity protection is fitted as standard,.

Email:nt_6MzX@mail.com

2021-05-07

Toshiba satellite m100 m105 fan toshiba terca a6 fan adda ab0705,sony vgn-e91b/b 19.5v 4.7a 6.5 x 4.4mm genuine new ac adapter,stealth touch p2/p3 ap108-12v ac

adapter 12vdc 9a i.t.e power.protec aec-4890 ac adapter 9vdc 1a used
2.5x5.5x11.4mm -(+)- rou,sony vgn-fj90ps2 19.5v 4.7a 6.5 x 4.4mm genuine new ac
adapter,acer aspire 3830tg 4830tg 5830tg cpu fan new,.